

# HARD SURFACE COATINGS



Oil Based	•	•					
Water Based				•	•		•
Solvent Based						•	
Solvent-Wax Based			•				
Vertical Surface	•	•				•	
Horizontal Surface		•	•	•	•	•	•
Interior Surface	•	•	•	•	•	•	•
Exterior Surface	•	•	•	•	•	•	•

Brickwork	•	•			•		
Cement				•			•
Clay Bricks (Paving)					•	•	
Crazy Paving		•		•	•		
Facebrick (Porous)	•						
Glazed Ceramic							
Granite / Porcelain						•	
Limestone (Porous)				•	•		
Marble / Slate / Travertine			•			•	
Quartzite / Rosestone, Sandstone (Porous) / Slasto / Stone (Porous)		•		•			
Quarry Tile (Porous)		•	•	•			
Terracotta Tiles			•	•			
Unglazed Tiles			•	•	•		

Finish	Satin	Matt or Gloss	Matt	Satin	Satin	Satin	Satin
Application	Brush	Brush	Brush or Cloth	Brush or Roller	Brush or Soft Broom	Brush or Cloth	Brush
Colours	Clear	Clear	Clear	Clear	Clear	Clear	Clear, white, light grey, dark grey, green or black
Spread Rate	Smooth Bricks: 4-8m <sup>2</sup> /lt Rough Bricks: 3-4m <sup>2</sup> /lt	Smooth Surfaces: 6-8m <sup>2</sup> /lt Rough Surfaces: 3-4m <sup>2</sup> /lt	20-30 m <sup>2</sup> /lt	8-10 m <sup>2</sup> /lt	7-10 m <sup>2</sup> /lt	10-12 m <sup>2</sup> /lt	Smooth Surfaces: 6-8m <sup>2</sup> /lt Rough Surfaces: 3-4m <sup>2</sup> /lt
Number Of Coats	Two	Two	One	Two to Three	Two	Two	Two
Touch Dry (at 20°C)	± 3-4 hours	Matt: ±20-30 minutes Gloss: ± 2-3 hours	± 3 hours	± 2-4 hours	± 2-3 hours	± 1-2 hours	± 2-4 hours
Re-Coating Time	± 24 hours	Matt: ±1 hour Gloss: ± 4 hours	Not Applicable	4 hours	2-3 hours	72 hours	2 hours
Clean Up	Nova 11	Nova 11	Nova 11	Warm soapy water	Warm soapy water	Thinners or Xylene	Warm soapy water
Pack Size	1lt, 5lt	1lt, 5lt	1lt, 5lt	5lt	5lt	1lt, 5lt	5lt